



## Construction Chemicals

### Fly Sealer

High-quality acrylic polymer emulsion sealer for porous surfaces. Use for sealing porous cement and gypsum-based surfaces before painting

### Description

Taneem sealer is a multipurpose sealer specially formulated to be used with cement and gypsum-based mortars & concrete, and putties to make the surface able to paint.

### Composition

Taneem Sealer is manufactured from selective acrylic co-polymers

### Advantage

- ✓ Fine particles to enhance penetration into different surfaces
- ✓ Reduce surface paint absorption
- ✓ Strength of weak surfaces before painting
- ✓ Excellent bonding with different substrates
- ✓ For indoor and outdoor uses
- ✓ Resistance to rain

### Technical Data

Base	Acrylic polymer- special additives
color	White
Density	1.35 Kg/L
Viscosity	125 Pa.sec
PH	8.5
Solid content	30%
Film thickness	25 microns
coverage	5 m <sup>2</sup> /liter (2 coats)

### Application procedures

- All surfaces should be cleaned and free from dust, oil, and grease
- Mix well before use
- Coverage rate may vary depending on surface conditions
- Leave the coat for 4 hours to dry before the next coat

### Storage

Shelf life is 12 months from the manufacturing date in a dry, covered storage area

### Packaging

Fly sealer is available in 9 - 125 -200 liters.