



Construction Chemicals

Technical datasheet

Taneem Gypsum putty

High quality Gypsum based putty modified with polymers, one component for smoothing internal surfaces before coating application.

Product description

Taneem Gypsum putty requires only addition of water on site. Smooth powders dissolve easy in water before application. Give smooth, hard and able to paint surface. Ideal for use as a painting putty on cement mortar, Gypsum mortar and Gypsum board.

Standers

Taneem Gypsum putty is formulated to comply with

- EN 13279 standers
- Egyptian standers 188-1/2013 C7

Product characteristics

- ✓ Exact mixing ratio and homogeneity of the mixture
- ✓ Excellent mixing and workability
- ✓ Breathable allows the substrate to breathe without de-lamination
- ✓ High bonding strength with smooth surfaces like fair face concrete

- ✓ White, smooth and able to be paint

Application

- Just add powder to water gradually then mixed together manually or with hand drill till reach a homogenous mixture.
- For best result add the suitable amount of water and keep mixing for 3 minutes to ensure proper mixing
- Use as joint filler for gypsum board and as skim coat for the full surface of gypsum board
- Applied with hand application technique using putty knife
- Leave the 1st layer to dry at least 3 hours before applying the 2nd layer
- Applicator should use the mixture around 120 minutes
- Applicator should wet and clean the surface before application



Construction Chemicals

Technical data

Base	Gypsum, special additive, selected polymers
Coverage for 1KG	Approx. 3.4 KG/m ²
Mixing ratio	70% water to powder weight
Setting time	About 120 Mint @ 25 C
Bending strength	≥ 1.0 N/mm ²
Compressive strength	≥ 2.0 1.0 N/mm ²
Recommended thickness	From 600 micron to 5 MM

Storage

Shelf life is 12 months from production date in a dry and covered storage area

Safety data

Taneem Gypsum putty is nontoxic material. PH value is near to 7 so it doesn't affect the human skin or make irritation for hand.

Please if the end product reach to eye or skin wash it good with clean water and soap.

Packaging

Taneem Gypsum putty is available in 12 Kg plastic bags

91, Industrial Zone, Belbies
10th of Ramadan Road, Sharkia, Egypt.
055 2900 190 055 2900 141



Construction Chemicals



91, Industrial Zone, Belbies
10th of Ramadan Road, Sharkia, Egypt.
055 2900 190 055 2900 141

www.flycc-eg.com

